











Composition: NPG Dioleate

Specifications: Parameter Range

Appearance Clear yellow liquid

Acid Value (mg KOH/g) 2 max.

Saponification Value (mg KOH/g) 172 – 186

Hydroxyl Value (mg KOH/g) 13 – 22

Water, % 0.2 max.

Color, Gardner 6 max.

Applications: DEHYLUB® 4016 US is an environmental friendly lubricant

which can be used in:

Aluminum Processing

• Metal Working Fluids

Steel Rolling Oils

Hydraulic Fluids

Forms of Delivery: Liquid in drums and bulk containers

Storage Information: Product stored in the original closed packaging under

ambient conditions should be stable for at least 2 years

Distributed by

Canoil Canada Ltd.

2525 Dunwin Drive Unit 8 Mississauga, Ontario Canada L5L 1R9 Phone: 905 820 2022 www.CanoilCanadaLtd.com

Updated: 27 - 09 - 17

Emery Oleochemicals GmbH T: +49 211 5611 2000

E: bl.europe@emeryoleo.com

Emery Oleochemicals LLC T: +1 513 762 2500

E: bl.americas@emeryoleo.com

Emery Oleochemicals (M) Sdn Bhd

T: +603 3326 8686

E: bl.asia@emeryoleo.com

Disclaimer: The content in this document is provided on an "as is" and "as available" basis purely for informational purposes and does not constitute any warranty, whether express, implied or statutory, including but not limited to warranties or guarantees of merchantability, filness or suitability for a particular purpose nor any representations of a binding nature. EMERY OLEOCHEMICALS EXPRESSLY DISCLAIMS ANY RESPONSIBILITY FOR THE SUITABILITY OF THE PRODUCTS FOR ANY SPECIFIC OR PARTICULAR PURPOSES INTENDED BY THE USER. Suggestions for the use and application of the products and guide for informational purposes only and you are advised to carry out any necessary steps to test the suitability of the products for your intended processes and purposes. You are solely responsible for compliance with all applicable laws and regulations in use of the products including any third party intellectual property rights and shall continue to bear all liability or risk arising from use of the products. All

